












BILL OF REINFORCING STEEL

SITE NO.

MARK	TYPE	PIN DIA.	LENGTH	Qty.	MASS	BENDING DIAGRAM
2001	17	0	3 320	64	500.39	
1502		0	18 000	4	113.04	
1503		0	10 200	8	128.11	
1504	17	166	7 645	2	24.01	
1505	17	166	7 100	2	22.29	
1506		0	6 925	2	21.74	
1507	17	166	6 550	2	20.57	
1508		0	6 375	2	20.02	
1509	17	166	6 005	2	18.86	
1510		0	5 850	2	18.37	
1511	17	166	5 455	2	17.13	
1512		0	5 300	2	16.64	
1513	17	166	4 910	2	15.42	
1514		0	4 750	2	14.92	
1515		0	4 500	21	148.37	
1516		0	4 475	7	49.18	
1517	19	0	4 395	8	55.20	
1518	17	166	4 360	2	13.69	
1519		0	4 250	1	6.67	
1520		0	4 200	2	13.19	
1521	17	166	3 815	2	11.98	
1522		0	3 650	2	11.46	
1523		0	3 255	1	5.11	
1523		0	3 090	1	4.85	
1523		0	2 925	1	4.59	

BILL OF REINFORCING STEEL






SITE NO.

MARK	TYPE	PIN DIA.	LENGTH	Qty.	MASS	BENDING DIAGRAM
1523		0	2 760	1	4.33	
1523		0	2 595	1	4.07	
1523		0	2 430	1	3.82	
1523		0	2 265	1	3.56	
1523		0	2 100	1	3.30	
1523		0	1 940	1	3.05	
1523		0	1 775	1	2.79	
1523		0	1 610	1	2.53	
1523		0	1 445	1	2.27	
1523		0	1 280	1	2.01	
1523		0	1 115	1	1.75	
1523		0	950	1	1.49	
1523		0	785	1	1.23	
1523		0	625	1	0.98	
1523		0	3 255	1	5.11	
1523		0	3 090	1	4.85	
1523		0	2 925	1	4.59	
1523		0	2 760	1	4.33	
1523		0	2 595	1	4.07	
1523		0	2 430	1	3.82	
1523		0	2 265	1	3.56	
1523		0	2 100	1	3.30	
1523		0	1 940	1	3.05	
1523		0	1 775	1	2.79	
1523		0	1 610	1	2.53	
1523		0	1 445	1	2.27	
1523		0	1 280	1	2.01	
1523		0	1 115	1	1.75	
1523		0	950	1	1.49	
1523		0	785	1	1.23	
1523		0	625	1	0.98	
1523		0	3 255	1	5.11	
1523		0	3 090	1	4.85	
1523		0	2 925	1	4.59	
1523		0	2 760	1	4.33	
1523		0	2 595	1	4.07	
1523		0	2 430	1	3.82	
1523		0	2 265	1	3.56	
1523		0	2 100	1	3.30	
1523		0	1 940	1	3.05	
1523		0	1 775	1	2.79	
1523		0	1 610	1	2.53	
1523		0	1 445	1	2.27	
1523		0	1 280	1	2.01	
1523		0	1 115	1	1.75	
1523		0	950	1	1.49	
1523		0	785	1	1.23	
1523		0	625	1	0.98	
1523		0	3 255	1	5.11	
1523		0	3 090	1	4.85	
1523		0	2 925	1	4.59	
1523		0	2 760	1	4.33	
1523		0	2 595	1	4.07	
1523		0	2 430	1	3.82	
1523		0	2 265	1	3.56	
1523		0	2 100	1	3.30	
1523		0	1 940	1	3.05	
1523		0	1 775	1	2.79	
1523		0	1 610	1	2.53	
1523		0	1 445	1	2.27	
1523		0	1 280	1	2.01	
1523		0	1 115	1	1.75	
1523		0	950	1	1.49	
1523		0	785	1	1.23	
1523		0	625	1	0.98	
1524	17	166	3 270	2	10.27	
1525		0	3 150	4	19.78	
1526		0	3 100	2	9.73	

BILL OF REINFORCING STEEL

SITE NO.

3

MARK	TYPE	PIN DIA.	LENGTH	Qty.	MASS	BENDING DIAGRAM
1527	17	166	2 720	2	8.54	
1528		0	2 550	2	8.01	
1529	7	0	2 185	20	68.61	
1530		0	2 000	2	6.28	
1531		0	1 500	48	113.04	
1532	10	0	1 465	9	20.70	
1033		0	3 030	26	61.84	
1034	60	0	2 240	26	45.72	

Total mass of reinforcing steel in kgs 1 840.70

Total volume of concrete in kgs