



## Validation Problem for Joint Checks as per ACI 318M-2014

### Input Data:


STAAD file	= RCDC-Staad-Demo -with RCC wall
Joint level	= 12.058 m
Column No. (RCDC)	= C22
Column Member no. (below joint)	= 1821
Column Member no.(above joint)	= 1831
Column Size	= 600 x 900
Height of column below Joint	= 4200 mm
Height of column Above Joint	= 4200 mm



3D View



**Top View**



**Element Numbers at Joint at 12.058m level**

*Note: STAAD command file is available at end of this document*

### **Relative Strength of Beams and Column at a Joint (Clause 18.7.3)**

**18.7.3.1** Columns shall satisfy 18.7.3.2 or 18.7.3.3.

**18.7.3.2** The flexural strengths of the columns shall satisfy

$$\sum M_{nc} \geq (6/5) \sum M_{nb} \quad (18.7.3.2)$$

where

$\sum M_{nc}$  is sum of nominal flexural strengths of columns framing into the joint, evaluated at the faces of the joint. Column flexural strength shall be calculated for the factored axial force, consistent with the direction of the lateral forces considered, resulting in the lowest flexural strength.

$\sum M_{nb}$  is sum of nominal flexural strengths of the beams framing into the joint, evaluated at the faces of the joint. In T-beam construction, where the slab is in tension under moments at the face of the joint, slab reinforcement within an effective slab width defined in accordance with 6.3.2 shall be assumed to contribute to  $M_{nb}$  if the slab reinforcement is developed at the critical section for flexure.

## RCDC Report for Flexural strength of Joint

### General Data:

Column No. : C22  
 Joint at Level : 12.058 m

	Column Below	Column Above
Member Number	1821	1831
Concrete Grade,fck (N/sqmm)	C25	C25
Steel Grade,fy (N/sqmm)	Fy420	Fy420
Column Size (mm)	600 X 900	600 X 900

### Check At Beam-Column Joints:

#### 1. Flexure Strength Of Joint:

##### Moment Capacity Calculations for Beam

Concrete Grade,fck = C25 N/sqmm  
 Steel Grade,fy = Fy420 N/sqmm

Beam Size	Beam angle w.r.t. column Ly	Torsion moment	Moment Capacity for Top Reinforcement				Moment Capacity for Bottom Reinforcement				Resultant Moment			
			Mu (kNm)	Ast Req (sqmm)	Ast Pro (sqmm)	Mu Cap (kNm)	Mu (kNm)	Ast Req (sqmm)	Ast Pro (sqmm)	Mu Cap (kNm)	Top @ D (kNm)	Top @ B (kNm)	Bot @ D (kNm)	Bot @ B (kNm)
(mm)	(deg)	(kNm)												
450 x 800	0	0	526.57	1986.13	2005.64	531.42	0	993.07	1013.44	277.05	531.42	0	277.05	0
500 x 800	90	0.69	622.63	2358.55	2382.72	628.58	0	1179.28	1266.8	345.01	0	628.58	0	345.01
300 x 900	180	0.48	464.11	1546.22	1588.48	475.96	0	773.11	886.76	273.66	475.96	0	273.66	0
400 x 600	270	0.46	562.24	3190.69	3546.97	613.22	0	1595.34	1626.2	310.84	0	613.22	0	310.84

**Effective Moment for Beam**

	<b>Along D</b>		<b>Along B</b>	
	Left	Right	Left	Right
Top (kNm)	475.96	531.42	613.22	628.58
Bottom (kNm)	273.66	277.05	310.84	345.01
Mnb (kNm)	MAX((Left Bottom + Right Top), (Left Top + Right Bottom))		MAX((Left Top + Right Bottom), (Right Top + Left Bottom))	
	805.07		958.23	

**Check for Column Flexural Capacity**

	<b>Along D</b>	<b>Along B</b>
Critical Load Combination Top	[11] : 0.9 (LOAD 1: LOAD CASE 1) -1.4 (LOAD 4: LOAD CASE 4 EQ-Y)	[11] : 0.9 (LOAD 1: LOAD CASE 1) -1.4 (LOAD 4: LOAD CASE 4 EQ-Y)
Pu Top (kN)	587	587
Mnc Top (kNm)	1531.58	999.35
Critical Load Combination Bot	[11] : 0.9 (LOAD 1: LOAD CASE 1) -1.4 (LOAD 4: LOAD CASE 4 EQ-Y)	[11] : 0.9 (LOAD 1: LOAD CASE 1) -1.4 (LOAD 4: LOAD CASE 4 EQ-Y)
Pu Bot (kN)	1103.74	1103.74
Mnc Bottom (kNm)	1166.72	767.91
Mnc (kNm)	2698.3	1767.26
	$\geq 1.2 \times Mnb$ , Hence OK	$\geq 1.2 \times Mnb$ , Hence OK

Where,

Mnb = Flexural Capacity of Beams in kN-m  
 Mnc Top = Flexural capacity of column above joint considered  
 Mnc Bottom = Flexural capacity of column below joint considered  
 Mnc = Mnc Top + Mnc Bottom, along D  
 Mnc = Mnc Top + Mnc Bottom, along B

Check for Column Flexural Capacity

Load Combination	Top Column	Bottom Column	Joint Flexure Check Along D				Joint Flexure Check Along B			
			Mnc Top (kNm)	Mnc Bottom (kNm)	Mnc Total (kNm)	Design Check Mnc Total/Mnb	Mnc Top (kNm)	Mnc Bottom (kNm)	Mnc Total (kNm)	Design Check Mnc Total/Mnb
4	Pu (kN)	Pu (kN)								
4	893.72	1878.87	1609.89	1353.97	2963.86	3.68	1055.88	904.33	1960.22	2.05
5	901.66	1910.29	1611.92	1361.03	2972.95	3.69	1057.35	909.43	1966.78	2.05
6	903.14	1913.55	1612.3	1361.76	2974.06	3.69	1057.62	909.96	1967.58	2.05
7	892.24	1875.62	1609.51	1353.23	2962.75	3.68	1055.61	903.81	1959.41	2.04
8	588.49	1107	1531.96	1167.56	2699.53	3.35	999.62	768.51	1768.14	1.85
9	596.42	1138.42	1533.99	1175.72	2709.71	3.37	1001.08	774.34	1775.42	1.85
10	597.91	1141.68	1534.37	1176.57	2710.94	3.37	1001.36	774.94	1776.3	1.85
11	587	1103.74	1531.58	1166.72	2698.3	3.35	999.35	767.91	1767.26	1.84

### Calculation of Column Capacity:

Column Above Joint at 12.058m level i.e. Bottom Node of Member 1831

### Member force table from RCDC:

Columns	Level	Analysis No	Load Comb	Load Comb	Load Comb	Location	P	Mx	My	ShearX	ShearY
			Ref No	Analysis No	Description	(m)	(kN)	(kNm)	(kNm)	(kN)	(kN)
C22	16.258 m	1831	1		1.4 (LOAD 1: LOAD CASE 1)	0	921.59	3.05	7.71	-3.95	2.7
			1		1.4 (LOAD 1: LOAD CASE 1)	4.2	842.18	-8.3	-8.87	-3.95	2.7
			2		1.2 (LOAD 1: LOAD CASE 1) +1.6 (LOAD 2: LOAD CASE 2)	0	962.34	5.99	9.63	-4.64	4.06
			2		1.2 (LOAD 1: LOAD CASE 1) +1.6 (LOAD 2: LOAD CASE 2)	4.2	894.27	-11.05	-9.84	-4.64	4.06
			3		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2)	0	897.69	4.72	8.49	-4.17	3.4
			3		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2)	4.2	829.62	-9.57	-9	-4.17	3.4
			4		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2) +1.4 (LOAD 3: LOAD CASE 3 EQ-X)	0	893.72	95.96	8.87	-4.38	60.01
			4		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2) +1.4 (LOAD 3: LOAD CASE 3 EQ-X)	4.2	825.65	-156.04	-9.52	-4.38	60.01
			5		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2) -1.4 (LOAD 3: LOAD CASE 3 EQ-X)	0	901.66	-86.51	8.11	-3.95	-53.21
			5		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2) -1.4 (LOAD 3: LOAD CASE 3 EQ-X)	4.2	833.59	136.89	-8.48	-3.95	-53.21
			6		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2) +1.4 (LOAD 4: LOAD CASE 4 EQ-Y)	0	903.14	3.69	69.3	-40.82	2.83
			6		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2) +1.4 (LOAD 4: LOAD CASE 4 EQ-Y)	4.2	835.07	-8.21	-102.12	-40.82	2.83
			7		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2) -1.4 (LOAD 4: LOAD CASE 4 EQ-Y)	0	892.24	5.75	-52.32	32.49	3.97
			7		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2) -1.4 (LOAD 4: LOAD CASE 4 EQ-Y)	4.2	824.17	-10.93	84.11	32.49	3.97
			8		0.9 (LOAD 1: LOAD CASE 1) +1.4 (LOAD 3: LOAD CASE 3 EQ-X)	0	588.49	93.19	5.33	-2.75	58.35
			8		0.9 (LOAD 1: LOAD CASE 1) +1.4 (LOAD 3: LOAD CASE 3 EQ-X)	4.2	537.44	-151.8	-6.22	-2.75	58.35
			9		0.9 (LOAD 1: LOAD CASE 1) -1.4 (LOAD 3: LOAD CASE 3 EQ-X)	0	596.42	-89.27	4.57	-2.32	-54.87
			9		0.9 (LOAD 1: LOAD CASE 1) -1.4 (LOAD 3: LOAD CASE 3 EQ-X)	4.2	545.37	141.13	-5.18	-2.32	-54.87
			10		0.9 (LOAD 1: LOAD CASE 1) +1.4 (LOAD 4: LOAD CASE 4 EQ-Y)	0	597.91	0.93	65.76	-39.19	1.17
			10		0.9 (LOAD 1: LOAD CASE 1) +1.4 (LOAD 4: LOAD CASE 4 EQ-Y)	4.2	546.86	-3.98	-98.81	-39.19	1.17
			11		0.9 (LOAD 1: LOAD CASE 1) -1.4 (LOAD 4: LOAD CASE 4 EQ-Y)	0	587	2.99	-55.86	34.12	2.31
			11		0.9 (LOAD 1: LOAD CASE 1) -1.4 (LOAD 4: LOAD CASE 4 EQ-Y)	4.2	535.95	-6.69	87.41	34.12	2.31

### Note:

For column moment capacity calculation, load combinations contain Earthquake load case should be considered.

Pu from all Eq load combinations which gives minimum moment capacity should be considered.


## Along D

Pu which gives Minimum Moment capacity

Moment Capacity, (Mnc top)

Pu = 587 kN

Mcap = 1531.58 kNm (refer below PM curve)






## Along B

Pu which gives Minimum Moment capacity

Moment Capacity, (Mnc top)

Pu = 587 kN

Mcap = 999.35 kNm (refer below PM curve)



Column below Joint at 12.058m level i.e. top Node of Member 1821

**Member force table from RCDC:**

Columns	Level	Analysis No	Load Comb	Load Comb	Load Comb	Location	P	Mx	My	ShearX	ShearY
			Ref No	Analysis No	Description						
C22	12.058 m	1821	1		1.4 (LOAD 1: LOAD CASE 1)	0	1825.85	5.75	18.9	-10.92	-0.49
			1		1.4 (LOAD 1: LOAD CASE 1)	4.2	1746.44	7.8	-26.95	-10.92	-0.49
			2		1.2 (LOAD 1: LOAD CASE 1) +1.6 (LOAD 2: LOAD CASE 2)	0	2201.23	17.3	12.33	-7.8	4.71
			2		1.2 (LOAD 1: LOAD CASE 1) +1.6 (LOAD 2: LOAD CASE 2)	4.2	2133.17	-2.47	-20.42	-7.8	4.71
			3		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2)	0	1962.65	12.66	13.78	-8.38	2.79
			3		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2)	4.2	1894.58	0.96	-21.42	-8.38	2.79
			4		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2) +1.4 (LOAD 3: LOAD CASE 3 EQ-X)	0	1946.94	170.52	14.14	-8.57	82.23
			4		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2) +1.4 (LOAD 3: LOAD CASE 3 EQ-X)	4.2	1878.87	-174.77	-21.84	-8.57	82.23
			5		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2) -1.4 (LOAD 3: LOAD CASE 3 EQ-X)	0	1978.36	-145.2	13.41	-8.2	-76.66
			5		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2) -1.4 (LOAD 3: LOAD CASE 3 EQ-X)	4.2	1910.29	176.69	-21.01	-8.2	-76.66
			6		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2) +1.4 (LOAD 4: LOAD CASE 4 EQ-Y)	0	1981.62	10.84	110.14	-57.02	2.04
			6		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2) +1.4 (LOAD 4: LOAD CASE 4 EQ-Y)	4.2	1913.55	2.29	-129.28	-57.02	2.04
			7		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2) -1.4 (LOAD 4: LOAD CASE 4 EQ-Y)	0	1943.68	14.48	-82.58	40.25	3.54
			7		1.2 (LOAD 1: LOAD CASE 1) +(LOAD 2: LOAD CASE 2) -1.4 (LOAD 4: LOAD CASE 4 EQ-Y)	4.2	1875.62	-0.37	86.43	40.25	3.54
			8		0.9 (LOAD 1: LOAD CASE 1) +1.4 (LOAD 3: LOAD CASE 3 EQ-X)	0	1158.05	161.56	12.51	-7.21	79.13
			8		0.9 (LOAD 1: LOAD CASE 1) +1.4 (LOAD 3: LOAD CASE 3 EQ-X)	4.2	1107	-170.71	-17.74	-7.21	79.13
			9		0.9 (LOAD 1: LOAD CASE 1) -1.4 (LOAD 3: LOAD CASE 3 EQ-X)	0	1189.47	-154.17	11.78	-6.83	-79.76
			9		0.9 (LOAD 1: LOAD CASE 1) -1.4 (LOAD 3: LOAD CASE 3 EQ-X)	4.2	1138.42	180.74	-16.91	-6.83	-79.76
			10		0.9 (LOAD 1: LOAD CASE 1) +1.4 (LOAD 4: LOAD CASE 4 EQ-Y)	0	1192.73	1.88	108.51	-55.65	-1.06
			10		0.9 (LOAD 1: LOAD CASE 1) +1.4 (LOAD 4: LOAD CASE 4 EQ-Y)	4.2	1141.68	6.34	-125.18	-55.65	-1.06
			11		0.9 (LOAD 1: LOAD CASE 1) -1.4 (LOAD 4: LOAD CASE 4 EQ-Y)	0	1154.8	5.52	-84.21	41.62	0.44
			11		0.9 (LOAD 1: LOAD CASE 1) -1.4 (LOAD 4: LOAD CASE 4 EQ-Y)	4.2	1103.74	3.68	90.53	41.62	0.44

**Note:**

For column moment capacity calculation load combinations contains Earthquake load case should be considered.

Pu from all Eq load combinations which gives minimum moment capacity should be considered.


## Along D

Pu which gives Minimum Moment capacity

Moment Capacity, (Mnc top)

Pu = 1103.74 kN

Mcap = 1166.72 kNm (refer below PM curve)




## Along B



Pu which gives Minimum Moment capacity  
Moment Capacity, (Mnc top)


Pu = 1103.74 kN

Mcap = 767.91 kNm (refer below PM curve)




### Calculation of Beam Capacity:


Beam @ 0 Location w.r.t. Column Ly – Load Comb 15 – Maximum Bending Moment




Beam @ 90 Location w.r.t. Colum Ly– Load Comb 16– Maximum Bending Moment



Beam @ 180 Location w.r.t. Colum Ly- Load Comb 14- Maximum Bending Moment



Beam @ 270 Location w.r.t. Column Ly– Load Comb 13– Maximum Bending Moment



Steps to Calculate Mcap of Beam at Ends:

1. Identifying the angle of Beam in plan w.r.t. column Ly. (Ly= Major direction & Lx = minor direction)
2. Finding out the maximum moment at end of the beam which is supported on column. Calculating the area of reinforcement required in beam for Major direction moment and torsion if any.
3. Detailing the beam with actual rebar diameters and rebar arrangements.
4. Calculating the Mcap of the beam for provided reinforcement.
5. If the beam is not orthogonal to the column axis, resolving the Mcap of that beam along column direction.



6. Finding out the effective moments for column along Ly and Lx of the column.

**Sample for calculation of Beam capacity:**


Beam @ 0 Location w.r.t. Colum Ly – Load Comb 15 – Maximum Bending Moment

Beam No	:	<b>B18</b>
Analysis Reference (Member) 12.058 m	:	6015
Beam Length	:	8000 mm
Breadth (B)	:	450 mm
Depth (D)	:	800 mm
Effective Depth (d)	:	745 mm
Design Code	:	ACI 318M - 2014
Beam Type	:	Ductile Beam (Special Frame)
Grade Of Concrete (f'c)	:	C25 N/sqmm
Grade Of Steel	:	Fy420 N/sqmm
Clear Cover (Cmin)	:	40 mm
Es	:	2x10 <sup>5</sup> N/sqmm
Mubal	:	1518.23 kNm
As,min (flex) (B)	:	1095 sqmm
As,nominal (Bn)	:	427.05 sqmm
As,min(user input)(B')	:	427.05 sqmm

Calculation of Ast for Mu:


For Longitudinal Reinf						
	Beam Bottom			Beam Top		
	Left	Mid	Right	Left	Mid	Right
Critical L/C - RCDC	8	2	-	5	9	4
Mu (kNm)	80.73	264.03	-	526.57	59.05	538.79
As (flex) (sqmm) (C)	289.15	965.02	-	1986.13	210.99	2035.37
Asc (flex) (sqmm) (A)	-	-	-	-	-	-
Tu (kNm)	-	-	-	-	-	-
Tcr/4 (kNm)	-	-	-	-	-	-
Al, min(sqmm)(Tor.) (D)	-	-	-	-	-	-
Al (sqmm) (Tor.) (E)	-	-	-	-	-	-
Al (Dist) (sqmm) (D)	-	-	-	-	-	-
Ast (sqmm)	435.82	1117.5	1146.08	1986.13	435.82	2035.37
AstPrv (sqmm)	633.4	1140.12	1266.8	2005.64	506.72	2292.16
Reinforcement Provided	5-#13	5-#13 4-#13	5-#13 5-#13	4-#19 3-#19	4-#13	4-#19 4-#19

Calculation of Mcap for provided reinforcement:



Ast provided	=	2005.64 sqmm
Xu-max/Deff	=	0.003 / 0.007
	=	0.428571
Xu-max	=	319.2857 mm
Fc Max	=	$Xu\text{-max} \times 0.85 \times f'_c \times B / 1000$
	=	2595.194 kN
Mu-lim	=	$Fc \text{ Max} \times (Deff - (0.85 \times Xu\text{-max})/2)$
	=	1581.261 kN-m
Check		Mu-lim > Mu , Beam to be designed as Singly reinforced section
a	=	$Ast \text{ provided} \times fy / (0.85 \times f'_c \times B)$
	=	88.09 mm
j	=	$(Deff - (0.5 \times a)) / Deff$
	=	0.940879
c	=	$a / 0.85$
	=	103.6363
Tensile force	=	$Ast \text{ provided} \times x \times fy$
	=	842.3688 kN
Xu-act	=	$a / 0.85$
	=	103.6363 mm
Mn	=	$Tensile \text{ force} \times j \times Deff$
	=	590.462 kN-m
Mcap	=	$Mn \times 0.9$
	=	531.42 kNm

## Design of Beam Column Joint for Distortional Shear (Clause 9.1)




**Fig. R18.8.4—Effective joint area.**

**18.8.4.1**  $V_n$  of the joint shall be in accordance with Table 18.8.4.1.

**Table 18.8.4.1—Nominal joint shear strength  $V_n$**

Joint configuration	$V_n$
For joints confined by beams on all four faces <sup>[1]</sup>	$1.7\lambda\sqrt{f'_c}A_j$ <sup>[2]</sup>
For joints confined by beams on three faces or on two opposite faces <sup>[1]</sup>	$1.2\lambda\sqrt{f'_c}A_j$ <sup>[2]</sup>
For other cases	$1.0\lambda\sqrt{f'_c}A_j$ <sup>[2]</sup>

Below is the snap showing shear to be considered for Joint check.



Joint shear,  $V_u = T_{b1} + C_{b2} - V_{c1}$

where,

$$C_{b1} = T_{b1} = 1.25 f_y A_{s1}$$

$$T_{b2} = C_{b2} = 1.25 f_y A_{s2}$$

$V_{c1}$  is column shear

## Output from RCDC

### Beams Along D

Angle w.r.t Column Ly	Reference Location	Width	Depth	Ast Pro Top	Ast Pro Bot
(deg)		(mm)	(mm)	(sqmm)	(sqmm)
0	Right	450	800	2005.64	1013.44
180	Left	300	900	1588.48	886.76

### Shear Checks

Conditions	AST-Total	V-Reinf	Vuy	Vj (Shear Demand)	B'	D'	Aj	Vn'	Vj < Vn'
	(sqmm)	(kN)	(kN)	(kN)	(mm)	(mm)	(sqmm)	(kN)	
Right Top + Left Bottom	2892.4	1518.51	805.07	713.44	600	900	540000	4590	OK
Left Top + Right Bottom	2601.92	1366.01	805.07	560.94	600	900	540000	4590	OK

### Beams Along B

Angle w.r.t Column Ly	Reference Location	Width	Depth	Ast Pro Top	Ast Pro Bot
(deg)		(mm)	(mm)	(sqmm)	(sqmm)
90	Right	500	800	2382.72	1266.8
270	Left	400	600	3546.97	1626.2

### Shear Checks

Conditions	AST-Total	V-Reinf	Vux	Vj (Shear Demand)	B'	D'	Aj	Vn'	Vj < Vn'
	(sqmm)	(kN)	(kN)	(kN)	(mm)	(mm)	(sqmm)	(kN)	
Right Top + Left Bottom	4008.92	2104.68	958.23	1146.46	900	600	540000	4590	OK
Left Top + Right Bottom	4813.77	2527.23	958.23	1569	900	600	540000	4590	OK

Example for calculation of effective width:

For Shear Along D of the Column

Beam Resting on the 0 degree w.r.t. Column Ly

Column Size = 600 x 900

Beam Size = 450 x 800

x = (600 – 450)/2

= 75 mm

Effective Width(B'1) = b + 2x

= 450+2x75

= 600 mm

Effective Width(B'2) = B+hc

= 450+800

Effective Width(B') = 1250 mm  
= Min (600,1250)  
= 600 mm

Effective Depth = D' (Column Depth)  
= 900 mm

Effective area = 600 x 900  
= 540000 sqmm

V-Reinf. calculation:  
Right top + left Bottom = 2005.64 + 886.76  
= 2892.4 Sqmm

V-reinf = 2892.4 x 420 x 1.25 x /1000  
= 1518.51 kN

Note:  
Beam capacity is calculated like explained in Flexural joint check.

#### Check At Beam-Column Joints:

##### **1. Flexure Strength Of Joint:**

##### **Moment Capacity Calculations for Beam**

Concrete Grade,fck = C25 N/sqmm  
Steel Grade,fy = Fy420 N/sqmm

Beam Size	Beam angle w.r.t. column Ly	Torsion moment	Moment Capacity for Top Reinforcement				Moment Capacity for Bottom Reinforcement				Resultant Moment			
			Mu (kNm)	Ast Req (sqmm)	Ast Pro (sqmm)	Mu Cap (kNm)	Mu (kNm)	Ast Req (sqmm)	Ast Pro (sqmm)	Mu Cap (kNm)	Top @ D (kNm)	Top @ B (kNm)	Bot @ D (kNm)	Bot @ B (kNm)
(mm)	(deg)	(kNm)												
450 x 800	0	0	526.57	1986.13	2005.64	531.42	0	993.07	1013.44	277.05	531.42	0	277.05	0
500 x 800	90	0.69	622.63	2358.55	2382.72	628.58	0	1179.28	1266.8	345.01	0	628.58	0	345.01
300 x 900	180	0.48	464.11	1546.22	1588.48	475.96	0	773.11	886.76	273.66	475.96	0	273.66	0
400 x 600	270	0.46	562.24	3190.69	3546.97	613.22	0	1595.34	1626.2	310.84	0	613.22	0	310.84


# Effective Moment for Beam

	Along D		Along B	
	Left	Right	Left	Right
Top (kNm)	475.96	531.42	613.22	628.58
Bottom (kNm)	273.66	277.05	310.84	345.01
Mnb (kNm)	MAX((Left Bottom + Right Top), (Left Top + Right		MAX((Left Top + Right Bottom), (Right Top + Left	
	805.07		958.23	

Vj (Shear Demand) = 1518.51 – 805.07  
 = 713.44 kN  
 Vn' = 1.7 x λ x Sqrt (f'c) x Aj  
 = 1.7 x 1 x Sqrt (25) x 540000  
 = 4590 kN  
 Check Vj < Vn'                      Ok



## RCDC DRAWING OUTPUT



STAAD SPACE

START JOB INFORMATION

ENGINEER DATE 17-Apr-19

END JOB INFORMATION

INPUT WIDTH 79

UNIT METER KN

JOINT COORDINATES

1 0 0 0; 2 8 0 0; 3 16 0 0; 4 24 0 0; 5 31.96 0 0; 6 0 0 5.71; 7 8 0 5.71;  
8 16 0 5.71; 9 24 0 5.71; 10 31.96 0 5.71; 11 0 0 14.61; 12 8 0 14.61;  
13 16 0 14.61; 14 24 0 14.61; 16 36.77 0 14.61; 17 46.08 0 10.87; 18 0 0 23.66;  
19 8 0 23.66; 20 16 0 23.66; 21 24 0 23.66; 22 31.96 0 23.66; 23 39.75 0 23.66;  
24 49.06 0 19.36; 25 0 0 32.61; 26 8 0 32.61; 27 16 0 32.61; 28 24 0 32.61;  
29 31.96 0 32.61; 30 37.83 0 32.61; 31 42.7 0 32.61; 41 0 4.2 0; 42 8 4.2 0;  
43 16 4.2 0; 44 24 4.2 0; 45 31.96 4.2 0; 46 0 4.2 5.71; 47 8 4.2 5.71;  
48 16 4.2 5.71; 49 24 4.2 5.71; 50 31.96 4.2 5.71; 51 0 4.2 14.61;  
52 8 4.2 14.61; 53 16 4.2 14.61; 54 24 4.2 14.61; 55 31.96 4.2 14.61;  
56 36.77 4.2 14.61; 57 46.08 4.2 10.87; 58 0 4.2 23.66; 59 8 4.2 23.66;  
60 16 4.2 23.66; 61 24 4.2 23.66; 62 31.96 4.2 23.66; 63 39.75 4.2 23.66;  
64 49.06 4.2 19.36; 65 0 4.2 32.61; 66 8 4.2 32.61; 67 16 4.2 32.61;  
68 24 4.2 32.61; 69 31.96 4.2 32.61; 70 37.83 4.2 32.61; 71 42.7 4.2 32.61;  
72 33.8399 4.2 5.71; 73 31.96 4.2 17.86; 74 37.8402 4.2 17.86;  
75 34.36 4.2 17.86; 76 34.36 4.2 14.61; 77 31.96 4.2 26.15;  
78 40.5707 4.2 26.15; 79 37.83 4.2 23.66; 80 37.83 4.2 26.15; 81 0 7.8576 0;  
82 8 7.8576 0; 83 16 7.8576 0; 84 24 7.8576 0; 85 31.96 7.8576 0;  
86 0 7.8576 5.71; 87 8 7.8576 5.71; 88 16 7.8576 5.71; 89 24 7.8576 5.71;  
90 31.96 7.8576 5.71; 91 0 7.8576 14.61; 92 8 7.8576 14.61; 93 16 7.8576 14.61;  
94 24 7.8576 14.61; 95 31.96 7.8576 14.61; 96 36.77 7.8576 14.61;  
97 46.08 7.8576 10.87; 98 0 7.8576 23.66; 99 8 7.8576 23.66;  
100 16 7.8576 23.66; 101 24 7.8576 23.66; 102 31.96 7.8576 23.66;  
103 39.75 7.8576 23.66; 104 49.06 7.8576 19.36; 105 0 7.8576 32.61;  
106 8 7.8576 32.61; 107 16 7.8576 32.61; 108 24 7.8576 32.61;  
109 31.96 7.8576 32.61; 110 37.83 7.8576 32.61; 111 42.7 7.8576 32.61;  
112 33.8399 7.8576 5.71; 113 31.96 7.8576 17.86; 114 37.8402 7.8576 17.86;

115 34.36 7.8576 17.86; 116 34.36 7.8576 14.61; 117 31.96 7.8576 26.15;  
118 40.5707 7.8576 26.15; 119 37.83 7.8576 23.66; 120 37.83 7.8576 26.15;  
121 0 12.0576 0; 122 8 12.0576 0; 123 16 12.0576 0; 124 24 12.0576 0;  
125 31.96 12.0576 0; 126 0 12.0576 5.71; 127 8 12.0576 5.71;  
128 16 12.0576 5.71; 129 24 12.0576 5.71; 130 31.96 12.0576 5.71;  
131 0 12.0576 14.61; 132 8 12.0576 14.61; 133 16 12.0576 14.61;  
134 24 12.0576 14.61; 135 31.96 12.0576 14.61; 136 36.77 12.0576 14.61;  
138 0 12.0576 23.66; 139 8 12.0576 23.66; 140 16 12.0576 23.66;  
141 24 12.0576 23.66; 142 31.96 12.0576 23.66; 143 39.75 12.0576 23.66;  
145 0 12.0576 32.61; 146 8 12.0576 32.61; 147 16 12.0576 32.61;  
148 24 12.0576 32.61; 149 31.96 12.0576 32.61; 150 37.83 12.0576 32.61;  
151 42.7 12.0576 32.61; 152 33.8399 12.0576 5.71; 153 31.96 12.0576 17.86;  
154 37.8402 12.0576 17.86; 155 34.36 12.0576 17.86; 156 34.36 12.0576 14.61;  
157 31.96 12.0576 26.15; 158 40.5707 12.0576 26.15; 159 37.83 12.0576 23.66;  
160 37.83 12.0576 26.15; 161 0 16.2576 0; 162 8 16.2576 0; 163 16 16.2576 0;  
164 24 16.2576 0; 165 31.96 16.2576 0; 166 0 16.2576 5.71; 167 8 16.2576 5.71;  
168 16 16.2576 5.71; 169 24 16.2576 5.71; 170 31.96 16.2576 5.71;  
171 0 16.2576 14.61; 172 8 16.2576 14.61; 173 16 16.2576 14.61;  
174 24 16.2576 14.61; 175 31.96 16.2576 14.61; 176 36.77 16.2576 14.61;  
178 0 16.2576 23.66; 179 8 16.2576 23.66; 180 16 16.2576 23.66;  
181 24 16.2576 23.66; 182 31.96 16.2576 23.66; 183 39.75 16.2576 23.66;  
185 0 16.2576 32.61; 186 8 16.2576 32.61; 187 16 16.2576 32.61;  
188 24 16.2576 32.61; 189 31.96 16.2576 32.61; 190 37.83 16.2576 32.61;  
191 42.7 16.2576 32.61; 192 33.8399 16.2576 5.71; 193 31.96 16.2576 17.86;  
194 37.8402 16.2576 17.86; 195 34.36 16.2576 17.86; 196 34.36 16.2576 14.61;  
197 31.96 16.2576 26.15; 198 40.5707 16.2576 26.15; 199 37.83 16.2576 23.66;  
200 37.83 16.2576 26.15; 201 31.96 4.2 16.085; 202 34.36 4.2 16.085;  
203 31.96 7.8576 16.085; 204 34.36 7.8576 16.085; 205 31.96 12.0576 16.085;  
206 34.36 12.0576 16.085; 207 31.96 16.2576 16.085; 208 34.36 16.2576 16.085;  
213 31.96 0 16.085; 214 34.36 0 16.085; 215 31.96 4.2 14.31;  
216 33.16 4.2 14.31; 217 31.96 7.8576 14.31; 218 33.16 7.8576 14.31;  
219 31.96 12.0576 14.31; 220 33.16 12.0576 14.31; 221 31.96 16.2576 14.31;  
222 33.16 16.2576 14.31; 223 34.36 4.2 14.31; 224 34.36 7.8576 14.31;

225 34.36 12.0576 14.31; 226 34.36 16.2576 14.31; 227 33.16 0 14.31;

### MEMBER INCIDENCES

1 1 41; 11 41 81; 21 81 121; 31 121 161; 101 2 42; 111 42 82; 121 82 122;  
131 122 162; 201 3 43; 211 43 83; 221 83 123; 231 123 163; 301 4 44; 311 44 84;  
321 84 124; 331 124 164; 401 5 45; 411 45 85; 421 85 125; 431 125 165;  
501 6 46; 511 46 86; 521 86 126; 531 126 166; 601 7 47; 611 47 87; 621 87 127;  
631 127 167; 701 8 48; 711 48 88; 721 88 128; 731 128 168; 801 9 49; 811 49 89;  
821 89 129; 831 129 169; 901 10 50; 911 50 90; 921 90 130; 931 130 170;  
1001 11 51; 1011 51 91; 1021 91 131; 1031 131 171; 1101 12 52; 1111 52 92;  
1121 92 132; 1131 132 172; 1201 13 53; 1211 53 93; 1221 93 133; 1231 133 173;  
1301 14 54; 1311 54 94; 1321 94 134; 1331 134 174; 1501 16 56; 1511 56 96;  
1521 96 136; 1531 136 176; 1601 17 57; 1611 57 97; 1701 18 58; 1711 58 98;  
1721 98 138; 1731 138 178; 1801 19 59; 1811 59 99; 1821 99 139; 1831 139 179;  
1901 20 60; 1911 60 100; 1921 100 140; 1931 140 180; 2001 21 61; 2011 61 101;  
2021 101 141; 2031 141 181; 2101 22 62; 2111 62 102; 2121 102 142;  
2131 142 182; 2201 23 63; 2211 63 103; 2221 103 143; 2231 143 183; 2301 24 64;  
2311 64 104; 2401 25 65; 2411 65 105; 2421 105 145; 2431 145 185; 2501 26 66;  
2511 66 106; 2521 106 146; 2531 146 186; 2601 27 67; 2611 67 107; 2621 107 147;  
2631 147 187; 2701 28 68; 2711 68 108; 2721 108 148; 2731 148 188; 2801 29 69;  
2811 69 109; 2821 109 149; 2831 149 189; 2901 30 70; 2911 70 110; 2921 110 150;  
2931 150 190; 3001 31 71; 3011 71 111; 3021 111 151; 3031 151 191; 4001 41 42;  
4002 42 43; 4003 43 44; 4004 44 45; 4005 46 47; 4006 47 48; 4007 48 49;  
4008 49 50; 4009 51 52; 4010 52 53; 4011 53 54; 4012 54 55; 4014 58 59;  
4015 59 60; 4016 60 61; 4017 61 62; 4018 62 79; 4019 65 66; 4020 66 67;  
4021 67 68; 4022 68 69; 4023 69 70; 4024 70 71; 4025 65 58; 4026 58 51;  
4027 51 46; 4028 46 41; 4029 66 59; 4030 59 52; 4031 52 47; 4032 47 42;  
4033 67 60; 4034 60 53; 4035 53 48; 4036 48 43; 4037 68 61; 4038 61 54;  
4039 54 49; 4040 49 44; 4041 69 77; 4042 62 73; 4043 55 215; 4044 50 45;  
4045 71 78; 4046 63 74; 4047 56 72; 4048 56 57; 4049 63 64; 4050 64 57;  
4051 50 72; 4052 72 45; 4053 73 201; 4054 73 75; 4055 74 56; 4056 75 74;  
4057 76 56; 4058 75 202; 4059 77 62; 4060 77 80; 4061 78 63; 4062 79 63;  
4063 70 80; 4064 80 79; 5001 81 82; 5002 82 83; 5003 83 84; 5004 84 85;  
5005 86 87; 5006 87 88; 5007 88 89; 5008 89 90; 5009 91 92; 5010 92 93;

5011 93 94; 5012 94 95; 5014 98 99; 5015 99 100; 5016 100 101; 5017 101 102;  
5018 102 119; 5019 105 106; 5020 106 107; 5021 107 108; 5022 108 109;  
5023 109 110; 5024 110 111; 5025 105 98; 5026 98 91; 5027 91 86; 5028 86 81;  
5029 106 99; 5030 99 92; 5031 92 87; 5032 87 82; 5033 107 100; 5034 100 93;  
5035 93 88; 5036 88 83; 5037 108 101; 5038 101 94; 5039 94 89; 5040 89 84;  
5041 109 117; 5042 102 113; 5043 95 217; 5044 90 85; 5045 111 118;  
5046 103 114; 5047 96 112; 5048 96 97; 5049 103 104; 5050 104 97; 5051 90 112;  
5052 112 85; 5053 113 203; 5054 113 115; 5055 114 96; 5056 115 114;  
5057 116 96; 5058 115 204; 5059 117 102; 5060 117 120; 5061 118 103;  
5062 119 103; 5063 110 120; 5064 120 119; 6001 121 122; 6002 122 123;  
6003 123 124; 6004 124 125; 6005 126 127; 6006 127 128; 6007 128 129;  
6008 129 130; 6009 131 132; 6010 132 133; 6011 133 134; 6012 134 135;  
6014 138 139; 6015 139 140; 6016 140 141; 6017 141 142; 6018 142 159;  
6019 145 146; 6020 146 147; 6021 147 148; 6022 148 149; 6023 149 150;  
6024 150 151; 6025 145 138; 6026 138 131; 6027 131 126; 6028 126 121;  
6029 146 139; 6030 139 132; 6031 132 127; 6032 127 122; 6033 147 140;  
6034 140 133; 6035 133 128; 6036 128 123; 6037 148 141; 6038 141 134;  
6039 134 129; 6040 129 124; 6041 149 157; 6042 142 153; 6043 135 219;  
6044 130 125; 6045 151 158; 6046 143 154; 6047 136 152; 6051 130 152;  
6052 152 125; 6053 153 205; 6054 153 155; 6055 154 136; 6056 155 154;  
6057 156 136; 6058 155 206; 6059 157 142; 6060 157 160; 6061 158 143;  
6062 159 143; 6063 150 160; 6064 160 159; 7001 161 162; 7002 162 163;  
7003 163 164; 7004 164 165; 7005 166 167; 7006 167 168; 7007 168 169;  
7008 169 170; 7009 171 172; 7010 172 173; 7011 173 174; 7012 174 175;  
7014 178 179; 7015 179 180; 7016 180 181; 7017 181 182; 7018 182 199;  
7019 185 186; 7020 186 187; 7021 187 188; 7022 188 189; 7023 189 190;  
7024 190 191; 7025 185 178; 7026 178 171; 7027 171 166; 7028 166 161;  
7029 186 179; 7030 179 172; 7031 172 167; 7032 167 162; 7033 187 180;  
7034 180 173; 7035 173 168; 7036 168 163; 7037 188 181; 7038 181 174;  
7039 174 169; 7040 169 164; 7041 189 197; 7042 182 193; 7043 175 221;  
7044 170 165; 7045 191 198; 7046 183 194; 7047 176 192; 7051 170 192;  
7052 192 165; 7053 193 207; 7054 193 195; 7055 194 176; 7056 195 194;  
7057 196 176; 7058 195 208; 7059 197 182; 7060 197 200; 7061 198 183;

7062 199 183; 7063 190 200; 7064 200 199; 7065 201 55; 7066 202 76;  
7067 203 95; 7068 204 116; 7069 205 135; 7070 206 156; 7071 207 175;  
7072 208 196; 7077 213 201; 7079 214 202; 7080 201 203; 7081 203 205;  
7082 202 204; 7083 204 206; 7086 205 207; 7087 206 208; 7088 215 50;  
7089 215 216; 7090 217 90; 7091 217 218; 7092 219 130; 7093 219 220;  
7094 221 170; 7095 221 222; 7096 216 223; 7097 218 224; 7098 220 225;  
7099 222 226; 7100 227 216; 7101 216 218; 7102 218 220; 7103 220 222;  
7104 76 223; 7105 116 224; 7106 156 225; 7107 196 226;

DEFINE MATERIAL START

ISOTROPIC CONCRETE

E 2.5e+07

POISSON 0.17

DENSITY 25

ALPHA 1e-05

DAMP 0.05

ISOTROPIC CONCDUMMY

E 2.5e+07

POISSON 0.17

DENSITY 0

ALPHA 1e-05

DAMP 0.05

END DEFINE MATERIAL

MEMBER PROPERTY INDIAN

1 11 21 31 101 111 121 131 201 211 221 231 301 311 321 331 401 411 421 431 -  
501 511 521 531 601 611 621 631 701 711 721 731 801 811 821 831 901 911 921 -  
931 1001 1011 1021 1031 1101 1111 1121 1131 1201 1211 1221 1231 1301 1311 -  
1321 1331 1701 1711 1721 1731 2001 2011 2021 2031 2101 2111 2121 2131 2701 -  
2711 2721 2731 2801 2811 2821 2831 2901 2911 2921 2931 3001 3011 3021 -  
3031 PRIS IX 1e-09 YD 0.7 ZD 0.7  
1501 1511 1521 1531 2201 2211 2221 -  
2231 PRIS AX 0.315 IX 1e-09 IY 0.00531562 IZ 0.0128625 YD 0.9 ZD 0.6  
1601 1611 2301 -  
2311 PRIS AX 0.2025 IX 1e-09 IY 0.00341719 IZ 0.00341719 YD 0.5 ZD 0.5

MEMBER PROPERTY INDIAN

4001 TO 4004 4019 TO 4028 4041 4042 4044 4048 TO 4050 4054 4056 4059 4063 -  
4064 5001 TO 5004 5019 TO 5028 5041 5042 5044 5048 TO 5050 5054 5056 5059 -  
5063 5064 6001 TO 6004 6019 TO 6028 6041 6042 6044 6054 6056 6059 6063 6064 -  
7001 TO 7004 7019 TO 7028 7041 7042 7044 7054 7056 7059 7063 7064 7088 7090 -  
7092 7094 PRIS AX 0.315 IX 1e-09 IY 0.00321562 IZ 0.0212625 YD 0.8 ZD 0.4  
4005 TO 4012 4015 TO 4018 4031 TO 4040 4045 TO 4047 4051 4052 4055 4057 4061 -  
4062 5005 TO 5012 5015 TO 5018 5031 TO 5040 5045 TO 5047 5051 5052 5055 5057 -  
5061 5062 6005 TO 6012 6015 TO 6018 6031 TO 6040 6045 TO 6047 6051 6052 6055 -  
6057 6061 6062 7005 TO 7012 7015 TO 7018 7031 TO 7040 7045 TO 7047 7051 7052 -  
7055 7057 7061 -  
7062 PRIS AX 0.54 IX 1e-09 IY 0.0162 IZ 0.03645 YD 0.8 ZD 0.45  
4060 5060 6060 -  
7060 PRIS AX 0.1725 IX 1e-09 IY 0.000760437 IZ 0.00808594 YD 0.75 ZD 0.23

MEMBER PROPERTY INDIAN

7077 7079 TO 7083 7086 7087 PRIS YD 3.55 ZD 0.35  
7100 TO 7103 PRIS YD 2.4 ZD 0.3

MEMBER PROPERTY INDIAN

4043 4053 4058 5043 5053 5058 6043 6053 6058 7043 7053 7058 7065 TO 7072 7089 -  
7091 7093 7095 TO 7099 7104 TO 7107 PRIS YD 4.2 ZD 0.35

MEMBER PROPERTY INDIAN

1801 1811 1821 1831 1901 1911 1921 1931 2401 2411 2421 2431 2501 2511 2521 -  
2531 2601 2611 2621 2631 PRIS YD 0.9 ZD 0.6

MEMBER PROPERTY

4029 5029 6029 7029 PRIS YD 0.6 ZD 0.4  
4030 5030 6030 7030 PRIS YD 0.8 ZD 0.5  
4014 5014 6014 7014 PRIS YD 0.9 ZD 0.3

SUPPORTS

1 TO 4 6 TO 9 11 TO 14 16 TO 21 23 TO 28 30 31 FIXED  
5 10 22 29 213 214 227 FIXED

CONSTANTS

BETA 90 MEMB 1901 1911 1921 1931 2601 2611 2621 2631 7077 7079 TO 7083 7086 -  
7087

MATERIAL CONCRETE MEMB 1 11 21 31 101 111 121 131 201 211 221 231 301 311 -  
321 331 401 411 421 431 501 511 521 531 601 611 621 631 701 711 721 731 801 -  
811 821 831 901 911 921 931 1001 1011 1021 1031 1101 1111 1121 1131 1201 -  
1211 1221 1231 1301 1311 1321 1331 1501 1511 1521 1531 1601 1611 1701 1711 -  
1721 1731 1801 1811 1821 1831 1901 1911 1921 1931 2001 2011 2021 2031 2101 -  
2111 2121 2131 2201 2211 2221 2231 2301 2311 2401 2411 2421 2431 2501 2511 -  
2521 2531 2601 2611 2621 2631 2701 2711 2721 2731 2801 2811 2821 2831 2901 -  
2911 2921 2931 3001 3011 3021 3031 4001 TO 4012 4014 TO 4042 4044 TO 4052 -  
4054 TO 4057 4059 TO 4064 5001 TO 5012 5014 TO 5042 5044 TO 5052 -  
5054 TO 5057 5059 TO 5064 6001 TO 6012 6014 TO 6042 6044 TO 6047 6051 6052 -  
6054 TO 6057 6059 TO 6064 7001 TO 7012 7014 TO 7042 7044 TO 7047 7051 7052 -  
7054 TO 7057 7059 TO 7064 7077 7079 TO 7083 7086 TO 7088 7090 7092 7094 7100 -  
7101 TO 7103

MATERIAL CONCDUMMY MEMB 4043 4053 4058 5043 5053 5058 6043 6053 6058 7043 -  
7053 7058 7065 TO 7072 7089 7091 7093 7095 TO 7099 7104 TO 7107

LOAD 1 LOADTYPE Dead TITLE LOAD CASE 1

SELFWEIGHT Y -1

MEMBER LOAD

4001 TO 4004 4019 TO 4028 4041 4042 4053 4059 4060 4063 4064 5001 TO 5004 -  
5019 TO 5028 5041 5042 5053 5059 5060 5063 5064 6001 TO 6004 6019 TO 6028 -  
6041 6042 6053 6059 6060 6063 6064 7065 7067 7069 UNI GY -14.285  
7001 TO 7004 7019 TO 7028 7041 7042 7053 7059 7060 7063 7064 7071 UNI GY -5

FLOOR LOAD

YRANGE 7 16 FLOAD -6 X RANGE 0 33 Z RANGE 0 33 GY  
YRANGE 7 16 FLOAD -6 X RANGE 31.96 36.77 Z RANGE 0 14.61 GY  
YRANGE 7 16 FLOAD -6 X RANGE 31.96 42.7 Z RANGE 23.66 32.61 GY  
YRANGE 7 16 FLOAD -6 X RANGE 31.96 39.75 Z RANGE 17.86 23.66 GY  
YRANGE 7 16 FLOAD -6 X RANGE 34.36 37.84 Z RANGE 14.61 17.86 GY  
YRANGE 7 10 FLOAD -6 X RANGE 36.77 49.06 Z RANGE 10.87 23.66 GY  
YRANGE 15 17 FLOAD -6 X RANGE 0 33 Z RANGE 0 33 GY  
YRANGE 15 17 FLOAD -6 X RANGE 31.96 36.77 Z RANGE 0 14.61 GY  
YRANGE 15 17 FLOAD -6 X RANGE 31.96 42.7 Z RANGE 23.66 32.61 GY  
YRANGE 15 17 FLOAD -6 X RANGE 31.96 39.75 Z RANGE 17.86 23.66 GY



YRANGE 15 17 FLOAD -6 X RANGE 34.36 37.84 ZRANGE 14.61 17.86 GY  
LOAD 2 LOADTYPE Live TITLE LOAD CASE 2  
FLOOR LOAD  
YRANGE 7 16 FLOAD -4 X RANGE 0 33 ZRANGE 0 33 GY  
YRANGE 7 16 FLOAD -4 X RANGE 31.96 36.77 ZRANGE 0 14.61 GY  
YRANGE 7 16 FLOAD -4 X RANGE 31.96 42.7 ZRANGE 23.66 32.61 GY  
YRANGE 7 16 FLOAD -4 X RANGE 31.96 39.75 ZRANGE 17.86 23.66 GY  
YRANGE 7 16 FLOAD -4 X RANGE 34.36 37.84 ZRANGE 14.61 17.86 GY  
YRANGE 7 10 FLOAD -2 X RANGE 36.77 49.06 ZRANGE 10.87 23.66 GY  
YRANGE 15 17 FLOAD -1.5 X RANGE 0 33 ZRANGE 0 33 GY  
YRANGE 15 17 FLOAD -1.5 X RANGE 31.96 36.77 ZRANGE 0 14.61 GY  
YRANGE 15 17 FLOAD -1.5 X RANGE 31.96 42.7 ZRANGE 23.66 32.61 GY  
YRANGE 15 17 FLOAD -1.5 X RANGE 31.96 39.75 ZRANGE 17.86 23.66 GY  
YRANGE 15 17 FLOAD -1.5 X RANGE 34.36 37.84 ZRANGE 14.61 17.86 GY  
LOAD 3 LOADTYPE None TITLE LOAD CASE 3 EQ-X  
JOINT LOAD  
161 TO 176 178 TO 183 185 TO 191 221 FX 35  
121 TO 136 138 TO 143 145 TO 151 219 FX 15  
81 TO 111 217 FX 7.5  
41 TO 71 215 FX 2  
LOAD 4 LOADTYPE None TITLE LOAD CASE 4 EQ-Y  
JOINT LOAD  
161 TO 176 178 TO 183 185 TO 191 221 FZ 35  
121 TO 136 138 TO 143 145 TO 151 219 FZ 15  
81 TO 111 217 FZ 7.5  
41 TO 71 215 FZ 2  
LOAD COMBINATION 11  
1 1.4  
LOAD COMBINATION 12  
1 1.2 2 1.0  
LOAD COMBINATION 13  
1 1.2 2 1.6  
LOAD COMBINATION 14

1 1.2 2 1.0 3 1.4  
LOAD COMBINATION 15  
1 1.2 2 1.0 3 -1.4  
LOAD COMBINATION 16  
1 1.2 2 1.0 4 1.4  
LOAD COMBINATION 17  
1 1.2 2 1.0 4 -1.4  
LOAD COMBINATION 18  
1 0.9 3 1.4  
LOAD COMBINATION 19  
1 0.9 3 -1.4  
LOAD COMBINATION 20  
1 0.9 4 1.4  
LOAD COMBINATION 21  
1 0.9 4 -1.4  
PERFORM ANALYSIS  
FINISH